

PAT-NO: JP401088835A  
DOCUMENT-IDENTIFIER: JP 01088835 A  
TITLE: CONTROLLER  
PUBN-DATE: April 3, 1989

INVENTOR-INFORMATION:  
NAME  
KOUNO, MICHIO

ASSIGNEE-INFORMATION:  
NAME COUNTRY  
TOSHIBA CORP N/A

APPL-NO: JP62247352

APPL-DATE: September 30, 1987

INT-CL (IPC): G06F009/06, G06F009/06

ABSTRACT:

PURPOSE: To reduce the extent of correction at the time of changing blocks by registering the number of a function module to be next executed in an information file for each function module and managing the execution order in accordance with this number.

CONSTITUTION: Parameter tables 1<SB>1</SB>&sim;1<SB>n</SB> are provided with next block number columns 2<SB>1</SB>&sim;2<SB>n</SB> respectively, and the numbers of blocks to be next executed are registered there. In case of insertion of a new block between a second block 5<SB>2</SB> and a third block 5<SB>3</SB>, the new block is defined as a fifth block 5<SB>5</SB> and a number B5 is given. Consequently, a number B3 in the next block number column of the

table I<SB>2</SB> of the second block is rewritten with the number B5 because the block 5<SB>5</SB> should be executed subsequently to the block 5<SB>2</SB>.

Since the block 5<SB>3</SB> should be executed following the block 5<SB>5</SB>,  
the number B3 is written in the next block number column of the table I<SB>5</SB>. The table I<SB>5</SB> of the fifth block is added subsequently to the table I<SB>n</SB>.

COPYRIGHT: (C)1989,JPO&Japio